

i/pvt

10/049349
JC13 PCT/PTO 30 JAN 2002
Express Mail No. ET99522115105

ROOT CANAL INSTRUMENT SUCH AS A
ROOT-CANAL REAMER AND METHOD FOR MAKING SAME

5 The present invention relates to the field of the
production of endodontic instruments for preparing
dental canals and more particularly to the canal
instruments of the dental reamer type which have a
working cross section called the "blade" which
10 comprises three flutes forming three cutting lips.

Canal instruments which have a working cross section
which comprises three flutes forming three cutting lips
are already known in the prior art.

15 In particular, this type of instrument is known from
the prior art French patent applications 96 04987 and
96 14347.

20 The instruments described in the aforementioned patent
applications have a circular symmetry of the order of
three or more depending on the number of cutting lips
of the instrument.

25 Thus, when the instrument is used in rotation in a
curved dental canal, the instrument follows the axis of
the canal by virtue of the equilibrium of the forces
applied to the instrument.

30 This type of instrument is satisfactory except when the
canal cannot be assimilated to a hole of circular cross
section. The reason is that in this latter case the
forces applied during the preparation of the canal are
no longer equilibrated and the trajectory of the
35 instrument risks deviating from the axis of the dental
canal. This deviation can have very serious
consequences since it can lead to the formation of an
incorrect path or even a perforation of the canal.

10049349 "013002

The aim of the present invention is to remedy the disadvantages of the prior art by making available an instrument whose blade makes it possible to eliminate this risk. This aim is achieved by deliberately
5 breaking the circular symmetry of the instrument in such a way that, as the resistance of the blade to bending is no longer the same in all directions, the point of the instrument is made to seek out the dental canal and to penetrate into the latter naturally.

10

Thus, the canal instrument according to the invention has a working cross section which comprises three flutes forming three cutting lips, and it is characterized in that the three cutting lips are
15 situated at the vertices of a triangle, not an equilateral one, but an isosceles one.

The present invention also relates to different methods for production of the canal instrument according to the
20 invention.

The invention will be better understood from the following description of an illustrative embodiment which is given as a nonlimiting example, reference
25 being made to the attached figures, in which:

Figure 1 illustrates a cross sectional view of a canal instrument of the prior art, where the three cutting lips are situated at the vertices of an equilateral
30 triangle;

Figure 2 illustrates a cross sectional view of a canal instrument according to the invention obtained by a first method of production;

35

Figure 3 illustrates a cross sectional view of a canal instrument according to the invention obtained by a second method of production; and

10049349-013002

Figure 4 illustrates a cross sectional view of a canal instrument according to the invention obtained by a third method of production.

5 The canal instrument (1) according to the invention is a canal instrument of the dental reamer type having a working cross section (10) which comprises three flutes (20, 21, 22) forming three cutting lips (30, 31, 32). It is characterized in that the three cutting lips (30, 10 31, 32) are situated at the vertices of an isosceles triangle.

Like all canal instruments of this type, the instrument according to the invention has a working cross section 15 (10), also called the "blade", whose active part is obtained by cutting and has a conical shape also obtained by cutting. The conical shape is obtained in most cases by progressively moving the cutting wheel away from the axis of the instrument as one proceeds 20 away from the point of the instrument.

A canal instrument (0) of the prior art, obtained by machining three identical flutes (20, 21, 22) forming three cutting lips (30, 31, 32) arranged at 120°, is 25 illustrated in Figure 1.

The present invention also relates to different methods for production of the canal instrument according to the invention.

30 A first possible way of producing the instrument (1) according to the invention consists in producing two flutes (20, 21) by performing two identical successive machining operations at 120°, then in producing the 35 third flute (22) by performing a third machining operation at a greater depth than the first two, as is illustrated in Figure 2.

It is also possible to make the depth of the third

200E10" 64E6400F

flute (22) such that it is greater than that of the first two flutes (20, 21) at the point of the working cross section (10) of the instrument and then becomes identical to the depth of the first two flutes (20, 21).

The depth of the third flute (22) can become identical to that of the first two flutes (20, 21) either at the end of the working cross section (10) or before the end of the working cross section (10).

A second possible way of producing the instrument (1) according to the invention consists in producing two flutes (20, 21) by performing two identical successive machining operations, at an angle greater than 120° , then in producing the third flute (22) by performing a third machining operation complementing the first two, as is illustrated in Figure 3.

A third possible way of producing the instrument (1) according to the invention consists in producing two flutes (20, 21) by performing two identical successive machining operations, at an angle less than 120° , then in producing the third flute (22) by performing a third machining operation complementing the first two, as is illustrated in Figure 4.

20049349-013002